

PEAK LS90 GL5 DIFF OIL

MINERAL AUTOMOTIVE GEAR OIL

DESCRIPTION & APPLICATION:

PEAK LS90 GL5 DIFF OIL is a heavy duty extreme pressure limited slip differential lubricant suitable for use in passenger cars, 4WD's, light and heavy commercial vehicles.

PEAK LS90 GL5 DIFF OIL may be used where API GL-5 SAE 90 gear oils are specified for helical, hypoid or spiral bevel axles, gear and steering boxes operating under high speed–shock load, high speed–low torque and low speed–high torque conditions.

BENEFITS:

- Excellent wear and corrosion protection
- High film strength for excellent wear protection
- Specially formulated for Limited Slip Differentials

TYPICAL CHARACTERISTICS*:

TEST	METHOD	TYPICAL VALUE
Density 15° C g/cm ³	ASTM D7042	0.891
Viscosity @ 40°C cSt	ASTM D7042	172
Viscosity @ 100°C cSt	ASTM D7042	16.0
Viscosity Index	ASTM D2270	100
Flash Point °C	ASTM D92	>230

PRODUCT SIZES:

PRODHVIT CODE	PACK SIZE	CTN QTY
PKGMLS90001	1 Litre	6
PKGMLS9002.5	2.5 Litre	6
PKGMLS90005	5 Litre	4
PKGMLS90020	20 Litre	
PKGMLS90060	60 Litre	
PKGMLS90205	205 Litre	
PKGMLS901000	1000 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API GL5
- ✓ API MT-1
- ✓ MIL-L-PRF-2105E

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 16 May 2022

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982