

PEAK 80W90 GEAR OIL

PREMIUM MINERAL GEAR OIL

DESCRIPTION & APPLICATION:

PEAK 80W90 is a heavy-duty multigrade GL-5 gear lubricant containing extreme pressure additives. It is recommended for hypoid or spiral bevel differential, gear, transfer and reduction gearboxes of automotive equipment.

PEAK 80W90 is commonly used in differentials and manual transmissions in passenger cars, light commercial, 4WD, earthmoving and agricultural applications.

BENEFITS:

- Excellent wear protection for prolonged gearbox life
- High load carrying ability
- Excellent resistance to corrosion and foaming
- Reduced transmission noise and smoother shifting
- Excellent non-chatter performance

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.882
Viscosity 40°C cSt	127.3
Viscosity 100°C cSt	13.9
Viscosity Index	106
Flash Point °C	>205
Colour	1.5

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKGM8090001	1 Litre	6
PKGM80900.5	2.5 Litre	4
PKGM8090005	5 Litre	4
PKGM8090020	20 Litre	
PKGM8090060	60 Litre	
PKGM8090205	205 Litre	
PKGM80901000	1000 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API GL-4 / GL-5
- ✓ API MT-1
- ✓ MACK GO-J
- ✓ SAE J2360

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 6 September 2023

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982