

PEAK JAY 460

PREMIUM MINERAL CIRCULATING OIL

DESCRIPTION & APPLICATION:

PEAK BRAE 460 is a high viscosity high quality mineral based machine circulating and lubricating oil. It will provide protection against rusting, oxidation and corrosion. Ideal for enclosed industrial gear systems where extreme pressure (EP) properties are not required.

BENEFITS:

- Excellent wear and corrosion protection provides high resistance to oxidation and helps to prolong oil life and lower maintenance costs
- Excellent demulsibility characteristics which allow these oils to maintain a high film strength coating on critical wear points of bearings and gear reducers and assure fast removal of water contamination
- Non-Zinc anti-wear additives make it suitable for use in circulating systems where silver plated components may be present

TYPICAL CHARACTERISTICS*:

TEST	METHOD	TYPICAL VALUE
Density 15° C g/cm ³	ASTM D7042	0.902
Viscosity @ 40°C cSt	ASTM D7042	440
Viscosity @ 100°C cSt	ASTM D7042	30
Viscosity Index	ASTM D2270	98
Flash Point °C	ASTM D92	>230

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKIMM460020	20 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ DIN 51517-1 Type C
- ✓ DIN 51517-2 Type CL

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 6 April 2022

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982