

PEAK BIO CHAIN BAR & DIELECTRIC FLUID

READILY BIODEGRADABLE FLUID

DESCRIPTION & APPLICATION:

PEAK BIO CHAIN BAR & DIELECTRIC FLUID is a highly eco-friendly chain bar lubricant especially designed to not only service the requirements of a normal chain bar oil, but to also protect our environment. The product is able to quickly break down into soil and water and is non-toxic to humans.

PEAK BIO CHAIN BAR & DIELECTRIC FLUID has a cutting edge formula targeted to both protect and extend the life of your chain, bar and sprockets. The specially selected tackifier ensures the fluid sticks to the components to avoid fling off.

PEAK BIO CHAIN BAR & DIELECTRIC FLUID has a resistance to flow of electricity carrying a dielectric strength of >35KV when exposed to currents or voltage.

BENEFITS:

- Outstanding Lubrication and adhesive properties.
- Highly Biodegradable into soil .
- Excellent dielectric strength.

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° Cg/cm ³	0.9206
Viscosity 40°CcSt	95
Viscosity 100°CcSt	20.7
Viscosity Index	242
Pour Point °C	-27
Dielectric Strength	38KV

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ Biodegradable >90%
- ✓ ISO 100

PRODUCT PACK SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKOBCC001	1 Litre	6
PKOBCC005	5 Litre	4
PKOBCC020	20 Litre	
PKOBCC0205	205 Litre	

PDS 117/04/2024

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982