

PEAK RADIATOR FLUSH

RADIATOR CLEANING ADDITIVE

DESCRIPTION & APPLICATION:

PEAK Radiator Flush is a non-acidic radiator flush containing organic salts. It safely removes scum, oily residue, sediments, rust, deposits and other degradation products from the cooling system.

PEAK Radiator Flush will not harm metals, plastics, rubber seals or gaskets in engine cooling systems of petrol, diesel, gas fuelled vehicles, trucks, buses, tractors, and heavy machinery.

BENEFITS:

- Contains corrosion inhibitors
- Easy to use
- Maximises cooling system efficiency
- Quickly and safely removes scum, oily residue, sediments, rust, deposits and other degradation products from the cooling system
- Requires no neutralizers
- Safe for all cooling systems including aluminium radiators

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKADPRF.325	325 ML	12

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Specific Gravity	1.1 (+/- 0.05)
Boiling Point °C	>106
pH	12-13
Physical State	Liquid
Colour	Blue

HOW TO USE:

- Ensure engine cooling system is cold prior to starting to prevent risk of burns.
- Drain cooling system completely, then fill system with water and PEAK Radiator Flush at a dose rate of Between 2.5 - 5% in water (between 250ml and 500ml per 10 Litres of cooling system capacity).
- Start the engine while idling making sure that the heater is turned on and run for 20 minutes.
- Allow the system to cool, drain and flush thoroughly with water.
- Refill the system with fresh water and inspect for leaks, tighten loose hose clamps and bolts were necessary.
- Drain and then refill the cooling system with the recommended PEAK coolant

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 8 February 2021

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982