



## PRODUCT INFORMATION SHEET

Re-Issue Date: 01/12/2020  
Page 1 of 2

# PREMIUM LONG LIFE GLOSS



### Description

**PREMIUM LONG LIFE GLOSS** is a clear solvent based acrylic sealer which enhances the natural beauty inherent in new or old slate floors.

**PREMIUM LONG LIFE GLOSS** imparts a high gloss finish, is highly resistant to yellowing from ultra violet light and imparts a long lasting finish to sealed surfaces.

### Application

**PREMIUM LONG LIFE GLOSS** is suitable for commercial and domestic slate areas, unglazed terracotta, paving bricks and most interior and exterior applications such as kitchens, family rooms, hearths, and patios.

Note: Newly laid areas need approximately 2-4 weeks to allow mortar and grout to cure and dry prior to sealing (depending on weather conditions).

### Features and Benefits

- ❖ UV stabilised to ensure your slate has the best possible protection against the sun's harmful rays
- ❖ Excellent re-coatability
- ❖ High resistance to yellowing
- ❖ High resistance to wear in heavy traffic areas
- ❖ High gloss finish on slate and other hard surfaces
- ❖ High solids formulation for long life
- ❖ Prevents staining and allows easy low cost maintenance

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied. Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.



## PRODUCT INFORMATION SHEET

Re-Issue Date: 01/12/2020  
Page 2 of 2

# PREMIUM LONG LIFE GLOSS

### Method of Use

**WARNING:** Ensure good ventilation to disperse solvent vapours. Keep away from naked flames, sparks etc

1. In order to determine the compatibility of **PREMIUM LONG LIFE GLOSS** with your slate floor a test area of one or two tiles should be attempted before sealing the entire floor. If the finish in this area meets with your requirements continue to seal the remaining tiles.
2. Surfaces to be sealed must be thoroughly clean and dry and free from grease, oil, paint, acid, efflorescence and traces of grout.
3. Newly laid areas need 4 - 6 days to allow mortar and grout to cure and dry prior to sealing. Slate which has been acid washed needs at least 4 weeks for slate to dry prior to sealing otherwise floor can turn white.
4. Surfaces previously sealed with slate sealers other than Tasman Slate Seal, **PREMIUM LONG LIFE GLOSS** or polished surfaces, must have all traces of old sealer and polish completely removed with suitable strippers.
5. Prior to sealing the slate, the slate should be cleaned with Tasmans TILE KLEEN. It should be continually washed until, after repeated washings, no slate dust appears in the wash up water. Allow at least 24 hours for the cleaned area to dry. Prior to sealing give the floor a quick vacuum.
6. Do not seal hot surfaces - all surfaces must be cool.
7. Apply 3-4 even generous coats of **PREMIUM LONG LIFE GLOSS** with a paint or lambswool applicator. Allow approximately 4 hours or until touch dry between coats.
8. Avoid heavy traffic for 48 hours after sealing.
9. To maintain seal in dry areas apply Tasman Slate Finish as per instructions. Otherwise simply apply Tasman Slate Seal to worn/dull areas as required.

**COVERAGE:** 1 litre will cover approximately 8-10m<sup>2</sup> with two coats.  
**CLEAN UP:** Brushes must be cleaned with Tasman SLATE SEAL SOLVENT or softened by soaking in Tasman's **PREMIUM LONG LIFE GLOSS** 10 minutes prior to reapplication.

### Packaging

◆ 1 Litre Metal Tins ◆ 4 Litre Metal Tins ◆ 10 Litre Metal Tins ◆ 20 Litre Metal Tins

### Health Hazard Information

See separate Health and Safety Data Sheet, available on request.

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied. Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.