



PRODUCT INFORMATION SHEET

HERITAGE

PENETRATING SEALER



Description

HERITAGE is a clear light buff coloured solution designed for application to a wide variety of porous surfaces in order to protect those surfaces from soiling and staining.

HERITAGE does not markedly change the appearance of the surface being treated.

Application

Suitable for commercial and domestic areas on the following surfaces:

- ❖ Unglazed tiles & quarry tiles
- ❖ Slate
- ❖ Terracotta
- ❖ Stone
- ❖ Brick
- ❖ Concrete

The product can also be used both internally and externally and is not subject to change in appearance and will not exhibit yellowing characteristics.

Features and Benefits

- ❖ Retains the natural look of the material being treated without markedly changing the original appearance of the surface.
- ❖ Helps to prevent staining caused by most common soils and food residues.
- ❖ Is suitable for use on a wide variety of surfaces including tiles, slate, terracotta, stone, brick and concrete.

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied. Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.



PRODUCT INFORMATION SHEET

HERITAGE

PENETRATING SEALER

Method of Use

WARNING: Ensure good ventilation to disperse solvent vapours. Keep away from naked flames, sparks etc

1. In order to determine the compatibility of **HERITAGE** with the surface to be sealed a test area should be attempted before sealing the entire surface. If the finish in this treated area meets with your requirements continue to seal the remaining area.
2. Surfaces to be sealed must be thoroughly clean and dry and free from grease, oil, paint, acid, efflorescence and traces of grout.
3. Newly laid areas need 7 - 10 days to allow mortar and grout to cure and dry prior to sealing.
4. Any stains and soiling on the tiles must be removed prior to sealing using a suitable detergent.
5. Allow the tiles to dry thoroughly prior to sealing by leaving for at least 24 hours after cleaning and washing.
6. Do not seal hot surfaces - all surfaces must be cool.
7. **HERITAGE** is applied neat and using a clean brush coat the entire surface to be treated and allow to dry. Apply a second coat after another 4 hours. On very porous surfaces up to 5 coats maybe required to provide adequate protection from soiling and staining.
8. Allow 24 hours for the product to fully cure before allowing full use of the treated area.
9. Clean all spills from the tile as quickly as possible to minimise penetration and staining. Tiles should be cleaned with TILE KLEEN, as a neutral detergent.
10. Coat tiles with **HERITAGE** every 6-12 months dependent on traffic and soiling

COVERAGE: One litre will cover approximately 15-25sq.m² dependent upon porosity of the tiles.

CLEAN UP: Brushes must be cleaned with Tasman SLATE SEAL SOLVENT

Packaging

◆ 1 Litre Metal Tins ◆ 4 Litre Metal Tins ◆ 10 Litre Metal Tins ◆ 20 Litre Metal Tins

Health Hazard Information

See separate Health and Safety Data Sheet, available on request.

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied. Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.