



# PRODUCT INFORMATION SHEET

# ENHANCE

## HI LITE SEALER

### Description

Tasman's **ENHANCE** is a breathable penetrating sealer which provides protection for concrete, terracotta tile, slate, pavers, limestone, brick, marble, granite and terrazzo while enhancing the colour of the surface to be sealed.

### Application

Tasman's **ENHANCE** is suitable for both commercial and domestic areas and areas such as kitchens, family rooms, hearths, bathrooms, shower recesses, patios and pool surrounds. It has been UV stabilised to ensure the sealed surface has the best possible protection against the sun's harmful rays. Treated surfaces become easier to clean, maintain, and keep looking good for longer. Tasman **ENHANCE** will prevent staining and allow low cost maintenance with **NO STRIPPING** ever. To reseal or touch-up, simply cover worn areas as needed.

### Features and Benefits

- ❖ Enrichment of natural colour of surface to be sealed
- ❖ Suitable for indoor and outdoor use
- ❖ Good resistance to abrasion, water, detergents and oil based stains.
- ❖ No stripping required, just reseal area
- ❖ Excellent levelling characteristics enabling surfaces to be sealed ranging from extremely porous tiles to dense tiles.
- ❖ Rapid hardness development.
- ❖ Fast set and tack-free times.

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied. Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.



# PRODUCT INFORMATION SHEET

# ENHANCE

## HI LITE SEALER

### Method of Use

**WARNING:** Ensure good ventilation to disperse solvent vapours. Keep away from naked flames, sparks etc

1. First test a small inconspicuous area. If the finish meets your requirements, continue to seal the remaining area
2. Surface to be sealed must be clean and dry, free from oil, grease, paint or acid, efflorescence loose flakes and grout residue.
3. New slate laid on sand and cement needs 4-6 weeks to allow mortar and grout to cure prior to sealing. New slate laid on adhesive can usually be sealed after 1-2 weeks.
4. Surfaces previously sealed with other sealers must have all traces of the old sealer removed with suitable strippers.
5. Prior to sealing, the surface to be sealed should be cleaned with Tasman's TILE KLEEN. It should be continually washed until after repeated washes no slate dust appears in the wash up water. Allow 24 hours for the cleaned area to dry. Prior to sealing give the floor a quick vacuum.
6. Do NOT apply when the temperature is less than 8 degrees Celsius.
7. Apply three to four even, generous coats of **ENHANCE** using a lambswool applicator. Allow approximately 2-4 hours between applications. Some surfaces are extremely porous and will require additional coats.  
**DO NOT USE A PAINT ROLLER OR PAINT BRUSH**
8. Avoid heavy traffic for 24 hours after sealing.
9. All spills and soils should be removed from treated surfaces as soon as possible

**COVERAGE:** One litre will cover approximately 15-25sq.m<sup>2</sup> dependent upon porosity of the tiles.

**CLEAN UP:** Brushes must be cleaned with Tasman SLATE SEAL SOLVENT

### Packaging

◆ 1 Litre Metal Tins ◆ 4 Litre Metal Tins ◆ 10 Litre Metal Tins ◆ 20 Litre Metal Tins

### Health Hazard Information

See separate Health and Safety Data Sheet, available on request.

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied. Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.