

## SYNPOWER™ FE SAE 0W-20

SynPower™ FE SAE 0W-20 is a premium full synthetic engine oil, formulated with the highest quality synthetic base oils and advanced additive technology. Designed to fulfill the latest standards of leading engine manufacturers.

SynPower™ FE SAE 0W-20 is manufactured using the latest advances in mid SAPS (Sulphated Ash, Phosphorus and Sulphur) additive technology, designed to provide maximum fuel efficiency whilst providing complete protection for vehicles running low viscosity engine oils. SynPower™ FE SAE 0W-20 also approved for Volvo VCC RBS0-2AE specification required for late model Volvo with 2.0L petrol or diesel engines.

### Specifications and Approvals

Synpower™ FE 0W-20*
ACEA C5
Volvo VCC RBS0-2AE <i>Approved</i>

\* Check owners' manual before use.

### Applications

Suitable for use in petrol, diesel and LPG engines where SAE 0W-20 ACEA C5 (previously A1/B1) specification is required.

Especially recommended for Volvo passenger cars with VAE (Volvo Engine Architecture) – Drive-E Powertrain.

Suitable for other passenger cars where ACEA A1/B1 or ACEA A5/B5 SAE 0W-20 is recommended.

### Features and Benefits

#### **Ultimate protection and performance**

SynPower engine oil is formulated with the highest quality base oils and latest additives to ensure ultimate protection and performance under all operating conditions. Designed to fulfil the latest standards of leading engine manufacturers.

#### **Approved by Volvo**

Officially approved by Volvo for service fill under Volvo VCC RBS0-2AE specification

#### **Fuel efficiency**

Low viscosity and special additives results in maximum reduction of friction which results in a lower fuel consumption.

#### **Excellent Cold Start Performance**

Instant oil flow at low temperatures provides easy cold start and optimal lubrication within seconds after ignition. Environment

#### **Wear Protection**

Provides ultimate protection against wear under all operating conditions.

# PRODUCT INFORMATION



## Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit [www.valvoline.com.au](http://www.valvoline.com.au) or contact the Technical Hotline on 1800 804 658 for product recommendations.

## Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

SynPower™ FE 0W-20	Typical
SAE Viscosity Grade	0W-20
Viscosity @ 100 °C, mm <sup>2</sup> /s, ASTM D445	9.2
Viscosity @ 40 °C, mm <sup>2</sup> /s, ASTM D445	48.0
Viscosity Index, ASTM D2270	177
Density @ 15 °C, kg/L, ASTM D4052	0.843
Total Base Number, mg KOH/g, ASTM D2896	8.0
CCS Viscosity, mPa.s @ -35 °C, ASTM D5293	<6200
Flash Point (COC), °C, ASTM D92	230
Pour Point, °C, ASTM D5950	-48

Note: SynPower™ FE SAE 0W-20 engine oil may be unsuitable for use in some engines, always consult owners' manual if in doubt.

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
872584	5L

## Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website [www.valvoline.com.au](http://www.valvoline.com.au)

## Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

## Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60 °C, exposed to hot sun or freezing conditions.

## Author:

FM - Effective 01-09-2021  
Replaces - 872584/01