

DEXRON®-VI ATF

DEXRON®-VI ATF (automatic transmission fluid) is formulated with premium synthetic base stocks and advanced additive technology, and meets all the stringent requirements of General Motors' DEXRON®-VI specification*, which is designed for the modern automatic transmissions in GM vehicles.

DEXRON®-VI ATF is officially licensed with GM and can be used in new and old GM automatic transmissions. It is fully back-serviceable and can be used wherever DEXRON®-II and/or DEXRON®-III are recommended.

Specifications and Approvals

DEXRON® VI ATF*
Dexron® VI <i>Approved</i>
Dexron® III
Dexron® II
Allison C4

*Check owners' manual before use.

Applications

Valvoline™ DEXRON®-VI ATF is officially licensed with GM and can be used in new and old GM automatic transmissions.

Features and Benefits

Superior Protection

Optimum protection against wear and tear, also under high stress working conditions.

Advanced additives

Modern additives protect against corrosion, oxidation, foaming and deposits.

Breakdown resistance

Synthetic base oils with balanced additive system, avoid breakdowns at higher operating temperatures

Enhanced friction properties

Premium base oils, viscosity index improvers, and friction modifiers result in special friction properties for smooth shifting. In addition, the product resists aging and has good thermal stability.

Consistent, stable viscosity

Excellent viscosity temperature properties even at very low temperatures. Highly stable viscosity over a long period.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvoline.com.au or contact the Technical Hotline on 1800 804 658 for product recommendations.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

Valvoline™ DEXRON® VI ATF	Typical
Viscosity @ 100 °C, mm ² /s, ASTM D445	6.2
Viscosity @ 40 °C, mm ² /s, ASTM D445	30.95
Viscosity Index, ASTM D2270	151
Density @ 15 °C, kg/L, ASTM D4052	0.846
Flash Point (COC), °C, ASTM D92	224
Pour Point, °C, ASTM D5950	-54

Note: Valvoline™ DEXRON® VI ATF may be unsuitable for use in some transmissions, always consult owners' manual if in doubt.

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
1272.20	20L
1272.51	205L

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website www.valvoline.com.au

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60 °C, exposed to hot sun or freezing conditions.

Author:

FM – Effective 03-07-2017
Replaces – 1272/04