

HD Chain and Cutter Bar Lube

A Product developed to provide efficient lubrication of cycle chains, all types of industrial chains and the demanding requirements of chain saw cutter bars.

Applications: HD Chain and cutter bar lube contains additives which provide “non-throw” properties and has the ability to penetrate in to the links providing lubrication and extending component life. It is recommended for industrial chains and chain saw cutter bar.

Features and Benefits

Enhanced Protection

Provides effective lubricant and penetration to the areas near the joints and moving parts of the chain. Contains anti-wear properties which minimises chain and sprocket wear whilst protecting against rust and corrosion during storage.

Extra Tacky

Excellent lubricating properties which resists the “throwing-off” effects of centrifugal force.

Wear Protection

Keeps the chain and bar clean by flushing away wood chips, gum, dust and removing sap and resin. Its unique chemistry emulsifies sap and resin minimising further build-up on the chain and bar.

High Viscosity

Protects against chain and bar wear in demanding forestry applications.

Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; speciality products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvoline.com.au or contact the Technical Hotline on 1800 804 658 for product recommendations.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

HD Chain & Cutter Bar Lube	Typical
Viscosity @ 100 °C, mm ² /s, ASTM D445	20.00
Viscosity @ 40 °C, mm ² /s, ASTM D445	216
Viscosity Index, ASTM D2270	108
Density @ 15 °C, kg/L, ASTM D4052	0.8945

Note: Always consult owners' manual if in doubt.

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
1249.51	205L
1249IBC	IBC

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website www.valvoline.com.au

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60 °C, exposed to hot sun or freezing conditions.

Author:

VP - Effective 08-09-2021
Replaces - 1249/05