

ATF DX-3

ATF DX-3 is premium mineral based automatic transmission fluid formulated to meet the requirements of the General Motors Specifications GM 6297M for a Dexron®III Fluid and Ford Mercon® for Ford transmission.

ATF DX-3 is also suitable for use in many other vehicle applications that require Dexron®III automatic transmission fluid including power steering systems.

Specifications and Approvals

ATF DX-3*
Allison C-4
Dexron® IIE
Dexron® IIIH
FORD M2C 166-H
FORD M2C 138-CJ
GM HN2126
GM 6297M
Mercon®

*Check owners' manual before use.

Applications

AFT DX-3 is a premium automatic transmission fluid specially formulated to meet the needs of compact transmissions, running at higher operating temperatures and with electronic control.

AFT DX-3 is recommended for use in automatic transmissions, where the manufacturer prescribes a GM Dexron IIE, Dexron III, or Ford Mercon fluid.

Note: Not for service use where Type F and M2C 33F and G Type Fluids are specified. Always check vehicle owner's manual before use.

Features and Benefits

Superior Protection

Through use of advanced additive chemistry ATF DX-3 fights the three major causes of transmission failure – heat, deposits and wear.

Enhanced viscosity control

Delivers improved performance and durability.

Cold start properties

Low temperature viscosity results improved shift performance at low temperatures.

Wear protection

Excellent wear protection enhances transmission life and shift consistency.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvoline.com.au or contact the Technical Hotline on 1800 804 658 for product recommendations.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

Valvoline™ ATF DX-3	Typical
Viscosity @ 100 °C, mm ² /s, ASTM D445	7.2
Viscosity @ 40 °C, mm ² /s, ASTM D445	35.07
Viscosity Index, ASTM D2270	177
Density @ 15 °C, kg/L, ASTM D4052	0.857
Flash Point (COC), °C, ASTM D92	208
Pour Point, °C, ASTM D5950	-45

Note: Valvoline™ ATF DX-3 may be unsuitable for use in some transmissions, always consult owners' manual if in doubt.

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
1215.01	1L
1215.04	4L
1215.20	20L
1215.52	60L
1215.51	205L

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website www.valvoline.com.au

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60 °C, exposed to hot sun or freezing conditions.

Author:

FM - Effective 03-07-2017
Replaces - 1215/04