

## Chain and Cutter Bar Lube

Chain and Cutter Bar Lube was developed to provide efficient lubrication of various types of chains for industrial chains and the demanding requirements of chain saw cutter bars.

### Applications

Chain and cutter bar lube contains additives which provide “non-throw” properties and has the ability to penetrate in to the links providing lubrication and extending component life. Suitable for use in chain drives including motor cycles, bicycles, industrial chains and chain saw cutter bar.

### Features and Benefits

#### Enhanced Protection

Provides effective lubricant and penetration to the areas near the joints and moving parts of the chain. Contains anti-wear properties which minimises chain and sprocket wear.

#### Extra Tacky

Excellent lubricating properties which resists the “throwing-off” effects of centrifugal force.

#### Wear Protection

Provides protection against rust, corrosion and oxidation

### Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit [www.valvoline.com.au](http://www.valvoline.com.au) or contact the Technical Hotline on 1800 804 658 for product recommendations.

### Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

Chain & Cutter Bar Lube	Typical
Viscosity @ 100 °C, mm <sup>2</sup> /s, ASTM D445	16.20
Viscosity @ 40 °C, mm <sup>2</sup> /s, ASTM D445	150.9
Viscosity Index, ASTM D2270	113
Density @ 15°C, kg/L, ASTM D4052	0.8910

Note: Always consult owners' manual if in doubt.

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
1243.01	1L
1243.05	5L
1243.20	20L
1243.51	205L
1243IBC	IBC

### Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website [www.valvoline.com.au](http://www.valvoline.com.au)

### Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

### Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

### Author:

VP - Effective 08-09-2021  
Replaces - 1243/04