

PRODUCT INFORMATION



Valvoline Professional Series (VPS) SAE 10W-30

Valvoline Professional Series (VPS) SAE 10W-30 engine oil is exclusive for professional workshops, designed and formulated to meet or exceed the latest specifications.

Valvoline Professional Series (VPS) SAE 10W-30 is a specific synthetic blend multigrade engine oil developed to meet the demanding requirements of the engine manufacturers, protecting your engine from start-up to shut down.

Valvoline Professional Series (VPS) SAE 10W-30 meets the latest industry standards of API SQ and ILSAC GF-7A, specially developed to help prevent Low-Speed Pre-Ignition (LSPI) issues in turbo charged gasoline direct injection (TGDI) engines and gasoline direct injection (GDI) engines. API SP is fully backwards compatible with API SN Plus/RC and can be used where API SN, SM, SL and SJ is recommended.

Valvoline Professional Series (VPS) SAE 10W-30 engine oils provide protection under various service conditions and meet the performance requirements of virtually all naturally aspirated, turbocharged and supercharged gasoline passenger cars and passenger SUV's and light commercial vehicles.

Specifications and Approvals

VPS SAE 10W-30 *
API SQ
API SP
API SN PLUS/RC
API SN
API SM, SL
API Resource Conserving
ILSAC GF-7A
ILSAC GF-6A
ILSAC GF-5
GM 6094M**

*Check owners' manual before use.

Applications

Valvoline Professional Series SAE 10W-30 synthetic blend motor oils focus to enhance engine durability and fuel efficiency, while maintaining drain intervals found in today's passenger cars.

Valvoline Professional Series SAE 10W-30 engine oils are suitable for use in passenger and light duty commercial vehicles fitted with petrol engines.

Please always consult the vehicle owners' manual before use.

Not recommended for use in diesel fuelled engines.

**Obsolete Specification

Features and Benefits

Professional Series Product Range

Synthetic Blend Workshop specific engine oil range to cover modern vehicles

Superior Protection

VPS engine oil fights the major causes of engine stress, heat, deposits and wear from Start-up to Shut down.

Advanced additive system

Provides excellent wear protection and enhances engine life without effecting emissions system life-time.

Viscosity Control

Delivers enhanced durability and lower oil consumption.

Wide operating conditions

Suitable for use in naturally aspirated and turbocharged petrol passenger vehicle and light commercial vehicles.

Start-up Protect

Excellent cold start properties and low temperature viscosity results in easy cold start whilst providing maximum cold start protection.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvoline.com.au or contact the Technical Hotline on 1800 804 658 for product recommendations.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

Valvoline Professional Series	Typical
SAE Viscosity Grade	10W-30
Viscosity @ 100 °C, mm ² /s, ASTM D445	11.38
Viscosity @ 40 °C, mm ² /s, ASTM D445	75.10
Viscosity Index, ASTM D2270	144
Density @ 15 °C, kg/L, ASTM D4052	0.8673
Total Base Number, mg KOH/g, ASTM D2896	8.0
CCS Viscosity, mPa.s @ -25 °C, ASTM D5293	6280
Flash Point (COC), °C, ASTM D92	224
Pour Point, °C, ASTM D5950	-42

Note: Valvoline Professional Series SAE 10W-30 engine oil may be unsuitable for use in some engines, always consult owners' manual if in doubt.

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
1278.20	20L
1278.28	208L
1278IBC	IBC
1278	Bulk

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website www.valvoline.com.au

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60 °C, exposed to hot sun or freezing conditions.

Author:

VP – Effective 11-12-2025

Replaces – 1278/08