

Synpower™ CVT

Synpower™ CVT is a premium full synthetic multi-vehicle transmission fluid for passenger cars and vans with a CVT (continuously variable transmission) gearbox.

Synpower™ CVT provides outstanding protection and lubrication of most belt and chain driven transmissions over a wide temperature range.

Specifications and Approvals

Synpower™ CVT *
Audi /VW TL 52180, 52516
BMW / Mini Cooper EZL 799A
Daihatsu Ammix CVTF-DC
FCA CVTF+4
Ford WSS-M2C933-A
Ford WSS-M2C928-A, Mercon® C
GM DEX-CVT, GM CVT
Honda CVT Fluid/Multi Matic Fluid (HMMF)
Honda HCF-2
Hyundai / Kia SP CVT-1
Mazda CVTF 3320
MB 236.20
Mitsubishi Dia Queen CVTF J1
Mitsubishi Diamond ATF SP III
Nissan NS-2, NS-1
Subaru e-CVTF
Subaru Lineartronic CV-30, CVTF-II
Subaru High torque CVTF
Subaru i-CVT F, i-CVT FG
Suzuki CVTF 3320, CVTF Green 1
Toyota TC, WS

*Check owners' manual before use.

Applications

Especially for belt and chain driven continuously variable transmissions.

Suitable for European, Asian and American passenger cars and vans.

The product is not meant for Hybrid CVT units (Toyota and Ford).

Do not mix other transmission oils.

Important Note: Vehicle manufacturers only recommend their own genuine or approved fluid during warranty period and do not recognize alternate products. CVT MV offers an excellent alternate for vehicles out of the warranty period. Always check vehicle owners' manual and warranty requirements before use.

Features and Benefits

Maximum protection

Maximum protection against wear and tear, also under high stress working conditions. Modern additives protect against corrosion, oxidation, foam and deposits

Consistent viscosity

Maximum viscosity temperature properties even at very low temperatures. Highly stable viscosity with long term multigrade advantages. Exactly the right friction properties under cold and hot driving circumstances.

Breakdown resistance

Premium quality base oils and a highly balanced additive system avoid breakdown situations even after long-time use

Fuel Economy properties

By smooth lubrication, the product has light fuel economy properties. Easy oil circulation gives better cooling and with that also light fuel savings

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvoline.com.au or contact the Technical Hotline on 1800 804 658 for product recommendations.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

Synpower™ CVT*	Typical
Viscosity @ 100 °C, mm ² /s, ASTM D445	7.0
Viscosity @ 40 °C, mm ² /s, ASTM D445	32.21
Viscosity Index, ASTM D2270	188
Density @ 15 °C, kg/L, ASTM D4052	0.849
Pour Point, °C, ASTM D5950	-45

Note: Synpower™ CVT may be unsuitable for use in some transmissions, always consult owners' manual if in doubt.

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
1330.05	5L
1330.20	20L
1330.28	208L

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website www.valvoline.com.au

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60 °C, exposed to hot sun or freezing conditions.

Author:

FM - Effective 20-02-2019
Replaces - 1330/04