



Wheel Bearing Grease

This grease is an NLGI No.2 inorganic clay base, high temperature, and non-melting grease. It has high oxidation and extreme mechanical stability and is recommended for passenger car wheel bearings, particularly vehicles fitted with disc brakes. It is also recommended for bearings in equipment operating at high temperatures and is satisfactory for use at temperatures up to 180°C.

Specifications and Approvals

Wheel Bearing Grease*

NLGI 2

Thickner - Inorganic

*Check owners' manual before use.

Applications

DO NOT MIX GREASES. Ensure that all bearings are washed out prior to repacking. Repack in accordance with acceptable practices recommended by the equipment manufacturer.

NOTE:

NO MELT No.2 GREASE is not recommended for use in the wheel bearings of trucks or semi-trailers.

Features and Benefits

No Melt

The bentone inorganic thickener it able to withstand extremely which temperatures as found in automotive disk brake applications

Multi-Purpose

Designed for use in automotive, and farming applications

High Oxidation

It has high oxidation and is extremely mechanical stable for wheel bearings in passenger cars, specially fitted with disk brakes.

Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvoline.com.au or contact the Technical Hotline on 1800 804 658 for product recommendations.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

Wheel Bearing Grease	Typical
NLGI Grade	2
Thickener Type	Inorganic
Colour	Amber
Appearance	Smooth
Worked Penetration, (25 °C)	260 - 290
Dropping Point, °C, ASTTM D2265	None
Oil Viscosity, @ 40 °C, cSt	500
Oil Viscosity, @ 100 °C, cSt	150
Viscosity Index, cSt	95
Water, % max	0.1

Note: Wheel Bearing Grease may be unsuitable for use in certain applications, always consult owners' manual if in doubt.

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
0749.73	500gm TUB

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website www.valvoline.com.au

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60 °C, exposed to hot sun or freezing conditions.

Author:

VP - Effective 07-09-2021
Replaces - 0749/04