

Engine Flush

Safely removes sludge and build-up from inside the engine. Non-solvent formulation that is safe for seal and gasket material.

Cleans oil channels and dissolves contaminants so that when the used engine oil is drained, sludge and sediments are taken out with the old oil. This improved way of changing oil prevents the new oil from being contaminated.

Easy to Use:

Run the engine until normal temperature is reached. Add 350ml to the crankcase and allow the engine to run at normal idle for five minutes, do not drive the vehicle while Engine Flush is working.

Drain the sump and change the oil filter (avoiding the hot engine oil). Replace oil filter and refill with the correct grade of Valvoline engine oil.

Note: Heavily sludged engines may require the oil pick up strainer to be checked to ensure no blockages to oil pump.

Features and Benefits

- Removes Contaminates
- Cleans the engine within 5 Minutes
- Clears Blocked Oil Channels
- Improves Oil Circulations
- Reduces Blow-By

Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvoline.com.au or contact the Technical Hotline on 1800 804 658 for product recommendations.

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
8613	350ml

PRODUCT INFORMATION



Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website www.valvoline.com.au

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Author:

FM - Effective 03-07-2017
Replaces - 8613/01