

Formula F Power Steering Fluid

FORMULA F Power Steering Fluid is specifically developed for use in select Ford power steering systems requiring Ford ESN-M2C 134D specification fluid. **FORMULA F Power Steering Fluid** is blended with premium mineral base oils and selected additives to provide maximum protection for Ford power steering system.

FORMULA F Power Steering Fluid is formulated from highly refined mineral oils and a superior additive system to have a high level of resistance to thermal degradation and oxidation, while providing excellent wear protection in heavily loaded gear systems.

FORMULA F POWER STEERING FLUID is suitable for Ford EL to FG series including FPV and Territory SX to SY series specifying Ford M2C134D power steering fluid.

Approvals and Performance Levels

Formula F Power Steering Fluid
API GL-4
Ford M2C- 134-D
Ford M2C-86-B

Features and Benefits

- Low temperature flow for smooth steering and control
- Maximum power steering protection
- Excellent wear protection
- Increased power steering component life
- Minimizes steering shudder
- Reduced power steering pump noise
- Protects against rust and corrosion

Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvoline.com.au or contact the Technical Hotline on 1800 804 658 for product recommendations.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

Formula F Power Steering Fluid	Typical
SAE Viscosity Grade	10W-30
API Gear Oil	GL-4
SAE Gear Oil	80W
Viscosity @ 100 °C, mm ² /s, ASTM D445	9.7
Viscosity @ 40 °C, mm ² /s, ASTM D445	60.7
Viscosity Index, ASTM D2270	143
Density @ 15 °C, kg/L, ASTM D4052	0.861
Pour Point, °C, ASTM D5950	-36

Note: Always consult owners' manual if in doubt.

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
9012.01	1L

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website www.valvoline.com.au

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Author:

VP - Effective 06-09-2021
Replaces - 9012/02