

VPS ProDetail Windscreen Wash Additive

VPS ProDetail Wash Additive has been specially formulated to clean glass surfaces as well as repel rain and reduce spotting. It is a blend of detergents and natural ingredients with eucalyptus scent to remove insect residue and grime, leaving a streak free finish for maximum visibility. Enhances driving visibility and hence, safety.

Easy to Use

Mix 20mL of VPS ProDetail Windscreen Wash Additive in 2L of water and add it directly to the windscreen washer fluid reservoir.

Features and Benefits

- Refreshing eucalyptus scent
- Provides streak free finish
- Prevents smearing
- Fine to plastic, paint work and rubber
- Added detergent improves performance and reduces spotting

Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvoline.com.au or contact the Technical Hotline on 1800 804 658 for product recommendations.

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
417001	5L
417002	20L

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website www.valvoline.com.au

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Author:

VP- Effective 06-09-2021

Replaces - 417001, 417002/01