

VPS ProDetail Wheel & Tyre Cleaner

VPS ProDetail Wheel and Tyre Cleaner is a blend of detergents and degreasing agents coupled with oxalic acid for the effective removal of dirt, grease, grime and the ever-present brake dust, in one easy application. Easily removes brake dust from wheels and tyres. Always refer to wheel manufacturer cleaning instruction prior to use.

Easy to Use

1. Apply to cold wheels
2. Dilute at 1:3 to be applied either manually or through a spray unit.
3. Allow up to 2 minutes for the product to penetrate.
4. Rinse

Please Note: Do not allow the product to dry on the surface

Features and Benefits

- Non-corrosive to glass and painted surfaces
- Citrus Fragrance
- Concentrated liquid suitable for economic automatic dispensing

Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvoline.com.au or contact the Technical Hotline on 1800 804 658 for product recommendations.

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
404002	20L
404006	200L

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website www.valvoline.com.au

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60 °C, exposed to hot sun or freezing conditions.

Author:

VP- Effective 06-09-2021
Replaces - 404002, 404006/01