

Ultrazorb

ULTRAZORB is a highly absorbent low density zeolite material for use where oils and liquids have to be conveniently removed from floors, around machinery or other locations.

ULTRAZORB when fully laden with absorbed liquid will not cake, is non-sticky and maintains its granular free flowing form facilitating easy and effective removal.

ULTRAZORB is available in 22 Liter bags.

Features and Benefits

- Ultrazorb has a high absorption capacity of 95-105% wt/wt
- Far less Ultrazorb is required to effectively and quickly absorb spilt liquids when compared to other type absorbents.
- Ultrazorb has a fast absorption rate because of the large contact surface area in association with high porosity.
- Oils and liquids absorbed in Ultrazorb are retained within the porous structure.
- Ultrazorb granules are individual particles which do not crush easily when subjected to pressure, making removal easy.
- Ultrazorb is easier to handle and use because of its low density.
- The complete absorption and granular properties makes for easy disposal in approved refuse locations.

Caution: Absorbed flammable material may remain hazardous. Treat with caution.

Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvoline.com.au or contact the Technical Hotline on 1800 804 658 for product recommendations.

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
6223	22L

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website www.valvoline.com.au

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60 °C, exposed to hot sun or freezing conditions.

Author:

VP - Effective 07-09-2021
Replaces - 6223/03