

VPS ProDetail Truck Wash

VPS ProDetail Truck Wash is a heavy duty concentrated formulation based on mild surfactants, dispersing agents and corrosion inhibitors. It is safe to use on all metals and painted surfaces. Truck Wash will rinse freely leaving a bright, streak free finish.

VPS ProDetail Truck Wash has been formulated to remove mud, carbon, tar and road grime with minimal effort. Truck Wash can be used on trucks, buses, cars and even building exteriors.

Application:

Manual Application:

- Dilute 1:20, apply by sponge or mop. Rinse off with fresh water.

Pressure Sprayer:

- Concentrations of 2-10% are recommended depending on level of cleaning required.
- Do not allow the product to dry on surface. Avoid applying the product to hot surfaces or in direct sunlight.

Features and Benefits

- Safe on all surfaces
- Free rinsing
- Streak free results every time
- Suitable for hard water
- Mild formulation ensuring operator safety

Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvoline.com.au or contact the Technical Hotline on 1800 804 658 for product recommendations.

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
402002	20L
402006	200L
402008	IBC

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website www.valvoline.com.au

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60 °C, exposed to hot sun or freezing conditions.

Author:

VP- Effective 06-09-2021

Replaces - 402002, 402006, 402008/01