

VPS ProDetail Prep Solvent

VPS ProDetail Prep Solvent quickly and easily removes road tar, grime, gum, adhesive residue, paint transfers, wax build-up and cosmoline from paint, glass and plastic. Spray or wipe application allows detailer to custom tailor product usage. Dual action solvents won't harm delicate clear coat finishes, or plastic. Perfectly prepares and cleans paint and trim for detailing. Excellent on door jambs and lower rocker panels.

Easy to Use

1. For best results use soft, clean towels when applying product. Product is not intended for dyed or freshly painted surfaces.
2. Soak cloth and apply to area to be cleaned, or spray area liberally.
3. Remove loosened dirt by turning cloth to a clean side and wiping clean

Features and Benefits

- Clear Liquid
- Ready-To-Use (no dilution required)
- Clear Coat & Body Shop Safe
- Quickly and easily removes grease, gum, paint transfers and tar.
- Saves time and money, wipe/on wipe off.
- Will not soften paint or plastic

Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvoline.com.au or contact the Technical Hotline on 1800 804 658 for product recommendations.

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
412002	20L
412006	200L

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website www.valvoline.com.au

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Author:

VP- Effective 06-09-2021
Replaces - 412002, 412006/01