

## VPS ProDetail Premium Car Wash

VPS ProDetail Premium Car Wash is a concentrated liquid soap formulated to quickly and effectively clean all surfaces. The excellent lubricating qualities and thick foaming action prevents scratching of delicate clear coated surfaces.

### Easy to Use:

1. Dilute solution with cold clean water (using a sponge at 5-10% or sprayer foam at 10-20%)
2. Rinse thoroughly with water.
3. Chamois or towel dry.

### Features and Benefits

- Highly concentrated formula
- Will not strip wax from vehicle
- Clear coat safe
- Unique plating action prevents scratches and enhances gloss

### **Keeping the world moving since 1866™**

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit [www.valvoline.com.au](http://www.valvoline.com.au) or contact the Technical Hotline on 1800 804 658 for product recommendations.

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
401002	20L
401006	200L

### **Health and Safety**

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website [www.valvoline.com.au](http://www.valvoline.com.au)

### **Protect the Environment**

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

### **Storage**

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

### **Author:**

VP- Effective 06-09-2021  
Replaces - 401002,401006/01