

## PROFLEET™ IS 10W-40

ProFleet™ IS 10W-40 is a premium full synthetic engine oil engineered to meet the latest European and protect the latest after treatment systems. It fulfills the Ultra High Performance Diesel (UHPD) recommendations of major engine manufacturers.

ProFleet™ IS 10W-40 unique formulation offers a lower Sulphated Ash, Phosphorus, and Sulphur (SAPS) content to protect the latest after treatment systems, such as Exhaust Gas Recirculation systems (EGR), Selective Catalytic Reduction (SCR) systems and Diesel Particulate Filters (DPF) after treatment systems. The engine oil can provide long-drain service intervals for trucks driving long distances as per the manufacturer's guidelines.

### Specifications and Approvals

PROFLEET™ IS 10W-40*
ACEA E8 (ACEA E6 - 2016)
ACEA E11 (ACEA E9 - 2016)
API CK-4
JASO DH-2
Caterpillar ECF-3, ECF-2
CUMMINS CES 20086
Detroit Diesel DDC93K222
MAN M 3477
Mack EOS-4.5
DTFR 15C110 (formerly MB 228.51)
DTFR 15C100 (formerly MB 228.31)
Renault VI RLD-4
VOLVO VDS-4.5

\*Check owners' manual before use.

### Applications

Suitable for heavy-duty diesel engines in trucks and buses as well as industrial vehicles.

Suitable for use in high performance Euro diesel engines with Exhaust Gas Recirculation (EGR), Selective Catalytic Reduction (SCR) systems and Diesel Particle Filters (DPF) after treatment systems. Fulfills the Ultra High Performance Diesel (UHPD) recommendations of major engine builders. Suitable for trucks and buses with long-drain oil refreshment periods.

(EGR: Exhaust Gas Recirculation)  
(SCR: Selective Catalytic Reduction)  
(DPF: Diesel Particle Filter)

### Features and Benefits

#### **Engine Cleanliness**

Keeps the engine clean and in good condition over the drain period. Unique high levels of dispersive technology for better soot and viscosity control and superior wear protection

#### **Extended Drain**

Extended service intervals and long-drain oil intervals as per manufacturers guidelines.

#### **Environment**

Lower SAPS catalyst compatible engine oil, suitable for the EGR/DPF and SCR Systems

#### **Wear protection**

Stronger oil film protects the engine against wear and corrosion.

#### **OEM compliant engine oil**

Suitable for use and approved by major engine manufacturers.

## Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit [www.valvoline.com.au](http://www.valvoline.com.au) or contact the Technical Hotline on 1800 804 658 for product recommendations.

## Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

PROFLEET™ IS SAE 10W-40	Typical
SAE Viscosity Grade	10W-40
Viscosity @ 100 °C, mm <sup>2</sup> /s, ASTM D445	14.35
Viscosity @ 40 °C, mm <sup>2</sup> /s, ASTM D445	93.1
Viscosity Index, ASTM D2270	159
Density @ 15 °C, kg/L, ASTM D4052	0.861
CCS Viscosity, mPa.s @ -25 °C, ASTM D5293	5900
Flash Point (COC), °C, ASTM D92	230
Pour Point, °C, ASTM D5950	-36

Note: Profleet™ IS 10W-40 engine oil may be unsuitable for use in some engines, always consult owners' manual if in doubt.

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
1450.20	20L
1450.28	208L
1450IBC	1000L

## Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website [www.valvoline.com.au](http://www.valvoline.com.au)

## Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

## Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60 °C, exposed to hot sun or freezing conditions.

## Author:

FM - Effective 18-09-2024  
Replaces - 1450/03