PRODUCT INFORMATION



Valvoline[™] Contact Cleaner

Valvoline[™] Contact Cleaner is a high quality spray to clean electrical contacts.

Applications:

- Switches
- Batteries
- Contact points
- Printed circuit board switches
- Multiple sockets

Directions for use:

Before use, carefully read the directions on the packaging.

Valvoline[™] Contact Cleaner should be at room temperature before use. The processing temperature should be between 5 to 30°C.

Shake before use.

Switch off electrical installations before treatment.

Spray the parts to be treated until the contamination has disappeared.

Contaminated contact cleaner should be regarded as chemical waste.

Only switch on the electric installation after the solvent has been evaporated.

Product Characteristics:

- Powerful jet spray
- High dissolving properties
- Leaves no residue
- Non-conductive
- Non-corrosive
- 360° valve

KEEPING THE WORLD MOVING SINCE 1866[™]

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife[™], the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit <u>www.valvoline.com.au</u> or contact the Technical Hotline on 1800 804 658 for product recommendations.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline[™] specifications, variations in these characteristics may occur.

Valvoline [™] Contact Cleaner	Typical
Basis	Aliphatic Hydrocarbons with Alcohol
Propellant	Carbon dioxide
VOC-Content	Approx. 97% w/w
Colour	Transparent
Scent	Characteristic
Relative density at 20°C	0,73 g/ml
Yield	3,8 g/sec
Refractive Index at 20°C	1,370
Vapor Pressure at 20°C	5,5 to 6,5 bar

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
887066	500 mL

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website www.valvoline.com.au

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Author: VP - Effective 06-09-2021 Replaces - 887066/01

KEEPING THE WORLD MOVING SINCE 1866[™]