

XLD Classic 15W-40 Engine Oil

XLD Classic 15W-40 multigrade engine oil is developed to meet the demanding requirements for classic vehicles, protecting your engine from start-up to shut down.

XLD Classic 15-40 engine oil is formulated with premium mineral base stocks and an additive system designed for older classic engines, ensuring the enhanced performance and protection whilst exceeding many of the toughest requirements.

Specifications and Approvals

XLD Classic Engine Oil*
SAE 15W-40
API SL
API CF

*Check owners' manual before use.

Applications

XLD Classic 15W-40 engine oil can be used in petrol, diesel and LPG commercial vehicles where API SL/CF SAE 15W-40 specifications are recommended.

Please consult the owner's manual before use.

Features and Benefits

Superior Protection

High Performance Engine Oil fights the major causes of engine stress, heat, deposits and wear from Start-up to Shut down.

Protects engine from wear

Excellent wear protection and enhances engine life without adversely effecting emissions system life-time.

Reduces deposits and maximum sludge

Protection Uses advances dispersant and detergent technology to help reduce sludge and keep engine clean.

Oxidation and Viscosity Control

Delivers improved deposits control, oxidation protection and reduced oil thickening to maintain durability.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvoline.com.au or contact the Technical Hotline on 1800 804 658 for product recommendations.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

XLD Classic Engine Oil	Typical
SAE Viscosity Grade	15W-40
Viscosity @ 100 °C, mm ² /s, ASTM D445	14.88
Viscosity @ 40 °C, mm ² /s, ASTM D445	111.4
Viscosity Index, ASTM D2270	138
Density @ 15 °C, kg/L, ASTM D4052	0.872
Total Base Number, mg KOH/g, ASTM S5293	9.8
CCS Viscosity, mPa.s @ -20 °C, ASTM D5293	6200
Flash Point (COC), °C, ASTM D92	236
Pour Point, °C, ASTM D5950	-36

Note: XLD Classic 15-40 engine oil may be unsuitable for use in some engines, always consult owners' manual if in doubt.

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
1387.01	1L
1387.05	5L

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website www.valvoline.com.au

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60 °C, exposed to hot sun or freezing conditions.

Author:

VP - Effective 02-09-2021
Replaces -1387/01