

## Valvoline™ Ceramic Grease

Valvoline™ Ceramic Grease is a high quality metal-free ceramic grease, to treat parts which are subjected to heavy workloads and/or exposed to very high temperatures.

---

### Applications:

- ABS brake systems
- Lambda sensors
- Brake parts
- Exhaust parts
- Screwed connections, which are exposed to high temperatures
- Industrial ovens

### Directions for use:

Before use, carefully read the directions on the packaging.

Valvoline™ Ceramic Grease should be at room temperature before use. The processing temperature should be between 5 to 30 °C. Shake before use.

Apply Valvoline™ Ceramic Grease.

The specific lubrication properties of Valvoline™ Ceramic Grease will be obtained after evaporation of the solvent (approx. 1 minute).

---

### Product Characteristics:

- Protects against electrolytic corrosion
- High thermal stability
- Resistant to chemicals and weather influences
- Resistant to water, salt and weak acids and bases
- Prevents wear and sticking
- Extremely suitable to mount ABS brake systems and lambda sensors
- Directed jet spray
- Simplifies the future removal

## Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit [www.valvoline.com.au](http://www.valvoline.com.au) or contact the Technical Hotline on 1800 804 658 for product recommendations.

## Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

Valvoline™ Ceramic Grease	Typical
Basis	Very fine Ceramic Particles
VOC-content	Approx. 68% w/w
Colour	White
Scent	Characteristic
Appearance	Pasty
Relative density at 20 °C	1,26 g/ml
Yield	1,65 g/sec
Vapor Pressure at 20 °C	3 to 4 bar
Temperature resistant	-40 °C to +1200 °C

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
887055	500 mL

## Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website [www.valvoline.com.au](http://www.valvoline.com.au)

## Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

## Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60 °C, exposed to hot sun or freezing conditions.

## Author:

VP - Effective 07-09-2021  
Replaces - 887055/01