

Cylval C 460

Cylval C 460 is a steam cylinder and value lubricant, covering all steam conditions from wet saturated up to high super heat. Cylval C 460 is a high viscosity oil, containing a small percentage of compounding matter. The use of specific base oils and compounding matter ensures that the final product has enhanced performance when used as a steam engine lubricant.

Features and Benefits

High viscosity mineral oil compounded with selected fatty oils provides high film strength ensures that the oil adheres to surfaces.

Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvoline.com.au or contact the Technical Hotline on 1800 804 658 for product recommendations.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

Cylval C 460	Typical
Density @ 15 °C, kg/L, ASTM D4052	0.8970
Viscosity @ 40 °C, mm ² /s, ASTM D445	452
Viscosity @ 100 °C, mm ² /s, ASTM D445	32.00
Viscosity Index, ASTM D2270	100

Note: Always consult owners' manual if in doubt.

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
2052.51	205L

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website www.valvoline.com.au

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60 °C, exposed to hot sun or freezing conditions.

Author:

VP - Effective 08-09-2021
Replaces - 2052/03