

Product Information



A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Lubricants - Engine Oil – Pleasure Craft Motor Oils

Version: 1126/03

4 STROKE MOTORCYCLE 15W-50

Premium semi- synthetic motorcycle oil

4- STROKE MOTORCYCLE OIL is designed specifically for motorcycles. The combination of semi-synthetic base oils and advanced additives provide the best for engine. Motorcycles place special demands on engine oil that automotive are not designed to handle. The wet clutch system, high RPMs and temperatures, and metals found in motorcycles require special properties for proper performance and protection.

Performance Levels/Approvals

API SM/CF
JASO MA

Applications

Valvoline motorcycle lubricants use semi-synthetic base oils and advanced additives to bring out the best in your 4 stroke Motorcycle, including Cruisers and off-road motorcycles.

*This is not a passenger car motor oil and as such it is not recommended for passenger car use.

¹ Check owners' manual before use

Features and Benefits

- High RPM Temperature Performance

The combination of synthetic and conventional base stock with optimized additive chemistry provides resistance against oxidation and wear.

- High Levels of Anti-wear

Specifically engineered to reduce engine wear at the sustained high rpm experienced motorcycle engines.

- Wet clutch protection

Specifically designed for motorcycle engines with and without wet clutch systems.

- Film strength

Semi-synthetic base oils and advanced additives provide maximum film strength.

- Advanced Detergency Technology

Ensures your outboards vital internal components stays factory clean for longer.

Product Information



A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. A Material and Safety Data Sheet (MSDS) is available on request via your local sales office or 1800 804 658 1800 804 658 or through our website www.valvoline.com.au.

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

4 Stroke Motorcycle	
SAE Viscosity Grade	15W-50
Viscosity @ 100° C, mm ² /s, ASTM D445	17.7
Viscosity @ 40° C, mm ² /s, ASTM D445	137
Viscosity Index, ASTM D2270	143
Viscosity, mPa.s -20° C	6100
Density @ 15° C, kg/L, ASTM D4052	0.871

Note: JASO MA motor oils may be unsuitable for use in some engines, consult owners' manual if in doubt.

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
1126.58	1 L
1126.51	205L

People Who Know, Use Valvoline™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvoline.com.au or contact the Valvoline Technical Hotline on 1800 804 658

Author:

FM – Effective 01-04-2013

Replaces – 1126/02