

## Valvoline™ EGR Cleaner

Valvoline™ EGR Cleaner is a high quality exhaust gas recirculation cleaner to dissolve deposits in the EGR valve, air intake system, manifold and inlet valves. To restore the air flow to the engine, improving power and acceleration and reducing exhaust smoke.

---

### Applications:

- EGR valve
- Air intake system
- Manifold
- Inlet valve

### Directions for use:

Before use, carefully read the directions on the packaging. For professional use only.

Valvoline™ EGR Cleaner should be at room temperature before use. The processing temperature should be between 5 to 30 °C. Shake before use.

Please refer to the owner's manual for the location of the hardware.

Loosen the hose between the turbo and air intake system.

Start the engine and allow to run at approx. 2000 rpm.

Spray Valvoline™ EGR Cleaner directly into the inlet of the manifold by repeatedly, briefly pressing the nozzle till the engine runs more smoothly.

Install the hose.

---

### Product Characteristics:

- Fast acting
- Leaves no residue
- Prevents the deposits of resin
- 360° valve

## Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit [www.valvoline.com.au](http://www.valvoline.com.au) or contact the Technical Hotline on 1800 804 658 for product recommendations.

## Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

Valvoline™ DPF Cleaner	
Basis	Solution of organic solvents
VOC-Content	100% w/w
Relative density at 20 °C	0,73 g/ml
Yield	2 - 3 g/sec
Vapor Pressure at 20 °C	2,5 to 3,5 bar

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
887071	500 mL

## Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website [www.valvoline.com.au](http://www.valvoline.com.au)

## Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

## Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60 °C, exposed to hot sun or freezing conditions.

## Author:

VP - Effective 27-05-2020  
Replaces - 887071/New