

Valvoline™ Gasket Remover

Valvoline™ Gasket Remover is a high quality spray for fast and easy removal of dried adhesives and seals, as well as hardened sealing materials in cars and machine parts.

Applications:

- Cylinder heads
- Gear boxes
- Exhausts
- Crankcases
- Sanitary fittings
- Water and oil pumps
- Electro engines

Directions for use:

Before use, carefully read the directions on the packaging.

Valvoline™ Gasket Remover should be at room temperature before use. The processing temperature should be between 5 to 30°C. Shake before use.

Cover lacquered and plastic parts

Apply Valvoline™ Gasket Remover in an equal layer on the parts to be treated and allow to take effect for approx. 10 minutes.

Carefully remove the dissolved residues with a filling-knife.

With persistent contamination, repeat the treatment.

Product Characteristics:

- User friendly
- High dissolving properties
- Optimum effect in view of high viscosity
- Non-conductive
- Slight gel structure
- Non-corrosive
- Directed jet spray
- 360° valve

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvoline.com.au or contact the Technical Hotline on 1800 804 658 for product recommendations.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

Valvoline™ Gasket Remover	Typical
Basis	Dimethoxymethane
VOC-content	Approx. 95% w/w
Colour	Transparent
Scent	Ether
Relative density at 20 °C	0,75 g/ml
Yield	1,0 - 1,5 g/sec
Vapor Pressure at 20 °C	2 to 3 bar
pH Value	Neutral

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
887063	500 mL

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website www.valvoline.com.au

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60 °C, exposed to hot sun or freezing conditions.

Author:

VP - Effective 06-09-2021
Replaces - 887063/01