

Valvoline™ Synpower™ JL C5 SAE 0W-20

Valvoline™ Synpower™ JL C5 SAE 0W-20 is a premium full synthetic engine oil specifically designed for latest generation direct injection FSI/TSI petrol, naturally aspirated, supercharged & turbocharged engines.

Valvoline™ Synpower™ JL C5 SAE 0W-20 provide protection under various service conditions and meet the performance requirements of naturally aspirated, turbocharged and supercharged petrol passenger cars, passenger SUV's providing higher levels of fuel efficiency. Valvoline™ Synpower™ JL C5 0W-20 is specially designed for use in modern petrol vehicles with the focus to reduce exhaust emissions, engine durability and improve fuel efficiency.

Valvoline™ Synpower™ JL C5 SAE 0W-20 meets the Jaguar Land Rover engine oil requirements of STJLR.51.5122, required for modern 3.0L and 5.0L, Turbocharged and Supercharged Jaguar, Land Rover and Range Rover petrol vehicles.

Specifications and Performance Levels

Valvoline™ Synpower™ JL C5 0W-20*
SAE 0W-20
ACEA C5
API SN
MB 229.71 <i>Approved</i>
Jaguar Land Rover STJLR.51.5122 <i>Approved</i>

* Check owners' manual before use.

Applications

Valvoline™ Synpower™ JL C5 SAE 0W-20 is a full synthetic engine oil for petrol, naturally aspirated, supercharged & turbocharged engines.

Valvoline™ Synpower™ JL C5 SAE 0W-20 is suitable for use in modern 3.0L and 5.0L, Turbo and Supercharged Jaguar, Land Rover and Range Rover petrol vehicles asking for STJLR.51.5122 specification oil.

Features and Benefits

Ultimate protection

Platinum Dealer engine oils is formulated with the highest quality base oils and latest additives to ensure ultimate protection and performance under all operating conditions. Designed to fulfill the latest standards of leading engine manufacturers.

Extended drain performance

Formulated for excellent product stability. Long lasting performance and suitable for long drain intervals.

Engine Cleanliness

Keeps engine extremely clean by minimizing deposits.

Wear Protection

Provides ultimate protection against wear under all operating conditions.

Fuel efficiency

Low viscosity and special additives result in maximum reduction of friction which results in a lower fuel consumption.

Excellent Cold Start performance

Instant oil flow at low temperature provides easy cold starts and optimal lubrication within seconds after ignition.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvoline.com.au or contact the Technical Hotline on 1800 804 658 for product recommendations.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

Valvoline™ Synpower™ JL C5 0W-20	Typical
SAE Viscosity Grade	0W-20
Viscosity @ 100 °C, mm ² /s, ASTM D445	8.2
Viscosity @ 40 °C, mm ² /s, ASTM D445	39.70
Viscosity Index, ASTM D2270	189
Pour Point, °C, ASTM D5950	-48
Total Base Number, mg KOH/g, ASTM D2896	7.9
Density @ 15 °C, kg/L, ASTM D4052	0.841
Flash Point (COC), °C, ASTM D92	226
CCS Viscosity, mPa.s @ -35 °C, ASTM D5293	<6200

Note: Valvoline™ Synpower™ JL C5 SAE 0W-20 engine oil may be unsuitable for use in some engines, always consult owners' manual if in doubt.

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
1418.28	208L

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website www.valvoline.com.au

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60 °C, exposed to hot sun or freezing conditions.

Author:

FM - Effective 01-09-2021
Replaces - 1418/01