



Valvoline™ ATF Pro +4™

Valvoline™ ATF Pro +4™ is a uniquely blended automatic transmission fluid that meets Chrysler Material Standard MS-9602 (ATF +4®).

Valvoline ATF Pro +4™ ensures the best conditions of operation for the most recent Chrysler transmission during their complete lifetime.

Specifications and Approvals

Valvoline™ ATF Pro +4™*
Chrysler MS9602 (ATF +4®) <i>Approved</i>
Chrysler MS7176E (ATF +3®) <i>Approved</i>
Chrysler MS7176D (ATF +2®) <i>Approved</i>
Chrysler MS7176 ATF +®) <i>Approved</i>

*Check owners' manual before use

Applications:

Valvoline™ ATF Pro +4™ is certified and approved for all Chrysler cars and trucks that requires ATF +4®, ATF +3®, ATF +2® or ATF +®

Suitable for use in some models of Dodge, Fiat, Jeep, Hyundai and Mitsubishi where these specifications are recommended.

Features and Benefits

Superior Protection

Superior protection against wear and tear, also under high stress working conditions.

Cold start properties

Provides excellent flow properties at low temperatures resulting in smooth power transfer and gear changes.

Wear protection

Excellent wear protection enhances transmission life and shift consistency.

Smooth operation

Smooth power transfer performance and maintains smooth shifting longer than conventional automatic fluids.

Breakdown resistance

Premium synthetic base oils, balanced additive system avoid breakdowns and stick-slip even after long-time use.

Viscosity Stability

Improved viscosity stability for consistent transmission operation

Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvoline.com.au or contact the Technical Hotline on 1800 804 658 for product recommendations.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

Valvoline™ ATF Pro +4™	Typical
Viscosity @ 100 °C, mm ² /s, ASTM D445	7.50
Viscosity @ 40 °C, mm ² /s, ASTM D445	34.00
Viscosity Index, ASTM D2270	198
Density @ 15 °C, kg/L, ASTM D4052	0.8510
Pour Point, °C, ASTM D5950	-48
Colour, Visual	Red

Note: Valvoline™ ATF Pro +4™ may be unsuitable for use in some transmissions, always consult owners' manual if in doubt.

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
866736	1L

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website www.valvoline.com.au

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60 °C, exposed to hot sun or freezing conditions.

Author:

VP - Effective 05-09-2021
Replaces - 866736/01